



ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com

California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

Thermostatic Chrome Plated Griddles

Standard Features

- Stainless steel exterior & interior
- Heavy duty 1" thick chrome plated griddle plate with 2mm thick, 14-ga stainless steel rear and side splashes
- Chrome plating reduces radiant heat into the kitchen, minimizes food sticking and flavor transfer, and can help lower energy use
- Stainless steel grease drawer: 6-3/4"W x 17-1/2"D x 2-1/2"H, 4-qt capacity
- Temperature range: 200°F – 450°F
- U-shaped 30,000 BTU burners per 12" section with standby pilots
- Independent thermostatic controls for each 12" section
- Stainless steel legs standard
- Standing pilot ignition with automatic gas shut-off if pilot goes out
- 12-3/4" working height with protruding front edge design to reduce operator contact with hot plate area
- Clearance to combustible constructions:
Rear: 6"
Sides: 4"– 6" depending on model
- Clearance to non-combustible construction: 0"
- 3/4" NPT rear gas connection and regulator standard

Optional Accessories

- Extended warranty up to 5 years

MODELS:

ATG-2424-C / ATG-3624-C / ATG-4824-C
ATG-6024-C



ATG-2424-C



ATG-3624-C



ATG-4824-C



ATG-6024-C



1 YEAR PARTS AND LABOR WARRANTY
5 YEAR FULL EXTENDED WARRANTY AVAILABLE



Conforms to ANSI
STD Z83.11b-2009 (2011)
Certified to CSA
STD 1.8B-2009 (2011)
Conforms to NSF/ANSI STD.4



REV. 07/26



ATOSA USA, INC.

Toll Free: 855-855-0399 Email: info@atosausa.com

www.atosa.com | www.atosausa.com



California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

SPECIFICATIONS




Models	Burners and Control Method	Gas Type	Intake-tube Presssure (in.W.C.)	Per BTU B.T.U./h	Total BTU B.T.U./h	Regulator	Work Area (inch)	Exterior Dimensions (inch)	Net Weight (lbs)	Gross Weight (lbs)
ATG-2424-C	2 Burners, Independent Thermostatic Control	NG	4	30,000	60000	4" w.c.	24×24	24×32×15 ^{1/4}	217	263
		LP	10	30,000	60000	10" w.c.				
ATG-3624-C	3 Burners, Independent Thermostatic Control	NG	4	30,000	90000	4" w.c.	36×24	36×32×15 ^{1/4}	315	374
		LP	10	30,000	90000	10" w.c.				
ATG-4824-C	4 Burners, Independent Thermostatic Control	NG	4	30,000	120000	4" w.c.	48×24	48×32×15 ^{1/4}	419	487
		LP	10	30,000	120000	10" w.c.				
ATG-6024-C	5 Burners, Independent Thermostatic Control	NG	4	30,000	150000	4" w.c.	60×24	60×32×15 ^{1/4}	536	618
		LP	10	30,000	150000	10" w.c.				

PLAN VIEW

ATG-2424-C





ATG-3624-C





Side View

ATG-4824-C



ATG-6024-C



Stainless steel knobs



Dripping hole



Dripping pan



Stainless steel legs

